



LPG Oil SL 10W-40

Product Code: S10006

LPG Oil SL 10W-40 is an universal high performance and fuel economy semi synthetic oil for use in gasoline and diesel engines of passenger car and light vans with or without turbocharger. **This product is not suitable for vehicles equipped with Diesel Particle Filters.**

LPG Oil SL 10W-40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

LPG Oil SL 10W-40 exceeds the following performance criteria:

Exceeds API SL/CF ACEA A3/B3 MB 229.1 VW 501.01/505.00

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W-40
Density @15°C	kg/m ³	ASTM D4052	874.4
Kin. Viscosity @40°C	cSt	ASTM D7042	92.4
Kin. Viscosity @100°C	cSt	ASTM D7042	13.8
Viscosity Index		ASTM D2270	152
Viscosity CCS @-25°, max.	cP	ASTM D5293	6950
Flash Point COC, min	°C	ASTM D92	201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.0
Sulphated Ash	%Wt	ASTM D874	1.3

