



Turbo Oil 10W-60

Product Code: S10048

Turbo Oil 10W-60 is a supreme performance motor oil based on 100% PAO FULLY synthetic technology with exceptional quality, delivering extreme performance both in gasoline, diesel and LPG fuelled engines in passenger cars with or without turbocharger, aiming at working under severe temperature and load conditions.

Turbo Oil 10W-60 is based on 100% high quality FULLY synthetic Poly Alpha Olefin (PAO) and ESTER oil in combination with an unique additive package to ensure the following properties:

- Excellent thermal and oxidation stability.
- Excellent dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

Turbo Oil 10W-60 exceeds the following performance criteria:

API SN/CF

ACEA A3/B4 (16)

MB 229.1

VW 502.00/505.00

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W-60
Density @15°C	kg/m ³	ASTM D4052	848
Kin. Viscosity @40°C	cSt	ASTM D7042	160
Kin. Viscosity @100°C	cSt	ASTM D7042	23.5
Viscosity Index		ASTM D2270	177
Viscosity CCS -30°, max.	cP	ASTM D5293	5500
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-42
Total Base Number	mgKOH/g	ASTM D2896	10.5
Sulphated Ash	%Wt	ASTM D874	1.1

