



**SUPER POWER®**

## SUPER POWER PREMIUM LUBRICANTS

### Turbo Oil 0W-40

Product Code: S10053

**Turbo Oil 0W-40** is a supreme performance fuel saving fully synthetic engine oil to be used in gasoline and diesel engines of the latest generation passenger car and light vans with or without turbo compressor.

**Turbo Oil 0W-40** is based on 100% high performance PAO (PolyAlphaOlefine) synthetic base oil in combination with a specially selected additive technology to ensure the following properties.

- Fuel saving properties.
- Excellent thermal and oxidation stability.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- High viscosity index in a wide range of ambient conditions.

**Turbo Oil 0W-40** exceeds the following performance criteria:

API SN/CF	ACEA A3/B4 (16)	MB-Approval 229.5	VW 502.00/505.00
BMW LL-01	Porsche A40	Renault RN0710	

#### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	0W-40
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	842
Kin. Viscosity @40°C	cSt	ASTM D7042	77
Kin. Viscosity @100°C	cSt	ASTM D7042	14.2
Viscosity Index		ASTM D2270	188
Viscosity CCS @-35°C	cP	ASTM D5293	5580
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	10
Sulphated Ash	%Wt	ASTM D874	1.1

