



Motor Oil ECOHY 0W-30 ULTRA

Product Code: S10051

Motor Oil ECOHY 0W-30 ULTRA is a high performance fuel saving engine oil based on FULLY synthetic and PAO technology to be used in gasoline and diesel engines of the latest generation passenger cars and light vans where a ACEA A5/B5 specification is required and suitable for all engines which require an ACEA C2, ILSAC GF-5 and PSA B71 2290 performance specification.

Motor Oil ECOHY 0W-30 ULTRA is based on 100% high performance PAO (PolyAlphaOlefine) synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Fuel saving properties.
- Long oil drain interval possible.
- Excellent thermal and oxidation stability.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.

Motor Oil ECOHY 0W-30 ULTRA exceeds the following performance criteria:

API SN/CF

ACEA C2-16

ACEA A5/B5

ILSAC GF-5

PSA B71 2290

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	0W-30
Density @15°C	kg/m ³	ASTM D4052	859
Kin. Viscosity @40°C	cSt	ASTM D7042	51
Kin. Viscosity @100°C	cSt	ASTM D7042	9.6
Viscosity Index		ASTM D2270	165
Viscosity CCS @-35°, max.	cP	ASTM D5293	5500
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	8.0
Sulphated Ash	%Wt	ASTM D874	0.79

