



SUPER POWER PREMIUM LUBRICANTS

Motor Oil LLP 5W-30 ULTRA

Product Code: S10045

Motor Oil LLP 5W-30 ULTRA is a long life performance and fuel economy LOW SAPS oil based on FULLY synthetic technology for use in next generation gasoline and diesel engines of passenger cars and light vans where a VW 504.00/507.00 has been required and also suitable for vehicles where MB 229.51 and BMW LL-04 are required. **Remark: this product is not suitable for R5 and V10 TDI engines and engines where VW 506.01 is being advised.**

Motor Oil LLP 5W-30 ULTRA is formulated with high performance PAO (PolyAlphaOlefine) synthetic base oil in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Compatible for engines equipped with other catalyst like TWC.

Motor Oil LLP 5W-30 ULTRA exceeds the following performance criteria:

API SN/CF	ACEA C3-16	VW 504.00/507.00
MB-Approval 229.51	BMW LL-04	Porsche C30

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	5W-30
Density @15°C	kg/m ³	ASTM D4052	853
Kin. Viscosity @40°C	cSt	ASTM D7042	65.4
Kin. Viscosity @100°C	cSt	ASTM D7042	11.7
Viscosity Index		ASTM D2270	180
Viscosity CCS -30°, max.	cP	ASTM D5293	4500
Flash Point COC	°C	ASTM D92	210
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	8.6
Sulphated Ash	%Wt	ASTM D874	0.7

