



Motor Oil LE 5W-40 PAO

Product Code: S10023

Motor Oil LE 5W-40 PAO is a high performance and fuel economy LOW SAPS engine oil based on FULLY synthetic with PAO technology for use in the latest model gasoline and diesel engines of passenger car and light vans with or without turbocharger.

Motor Oil LE 5W-40 PAO is developed on compatibility in engines which are equipped with an exhaust gas after treatment system.

Motor Oil LE 5W-40 PAO is based on high performance FULLY synthetic base oil, in combination with PAO and specially selected additive packages, to ensure the following properties:

- LOW SAPS technology.
- Fuel saving properties.
- Good thermal and oxidation stability.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.

Motor Oil LE 5W-40 PAO exceeds the following performance criteria:

API SN/CF	ACEA C3-16	MB 229.51	VW 502.00/505.01
BMW LL-04	Porsche A40	Ford M2C917A	Renault RN 0700/0710

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	5W-40
Density @15°C	kg/m ³	ASTM D4052	849.1
Kin. Viscosity @40°C	cSt	ASTM D7042	66.86
Kin. Viscosity @100°C	cSt	ASTM D7042	12.84
Viscosity Index		ASTM D2270	196
Viscosity CCS -30°, max.	cP	ASTM D5293	5030
Flash Point COC	°C	ASTM D92	>218
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	8.4
Sulphated Ash	%Wt	ASTM D874	0.8

