



Motor Oil CX 5W-30 PAO

Product Code: S10033

Motor Oil CX 5W-30 PAO is a high performance and fuel saving LOW SAPS engine oil based on FULLY synthetic with PAO technology for use in the latest model gasoline and diesel engines of passenger car and light vans with or without turbocharger.

Motor Oil CX 5W-30 PAO is developed on compatibility in engines which are equipped with an exhaust gas after treatment system.

Motor Oil CX 5W-30 PAO is based on high performance FULLY synthetic base oil, in combination with PAO and specially selected additive packages, to ensure the following properties:

- LOW SAPS technology.
- Extended fuel saving properties.
- Good thermal and oxidation stability.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.

Motor Oil CX 5W-30 PAO exceeds the following performance criteria:

API SN/CF ACEA C3-16 MB 229.52 / 229.51 / 229.31
 BMW LL-04 VW 502.00/ 505.01 Renault RN0700 Dexos™2

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	5W-30
Density @15°C	kg/m ³	ASTM D4052	849.6
Kin. Viscosity @40°C	cSt	ASTM D7042	60.7
Kin. Viscosity @100°C	cSt	ASTM D7042	11.73
Viscosity Index		ASTM D2270	193
Viscosity CCS -30°, max.	cP	ASTM D5293	4610
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	8.2
Sulphated Ash	%Wt	ASTM D874	0.78

