



**SUPER POWER®**

## SUPER POWER PREMIUM LUBRICANTS

### XR-1 Racing Oil 20W-60

Product Code: S10078

**XR-1 Racing Oil 20W-60** is a supreme performance fully synthetic engine oil which specially design to survive in severe conditions, including continuous high loading, high RPM, extreme hot and humid weather. Proven formula by racing team in real races, to be used in Endurance race and competition race.

**XR-1 Racing Oil 20W-60** is based on 100% high performance PAO (PolyAlphaOlefine) and Ester in combination with a specially selected additive technology to ensure the following properties.

- Supreme stability in oil temperature and oil pressure
- Ultimate shear and wear stability.
- Excellent oil circulation, to provide engine protection.
- High viscosity index in a wide range of ambient conditions.

**XR-1 Racing Oil 20W-60** exceeds the following performance criteria:  
Excess current specifications

#### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	20W-60
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	875
Kin. Viscosity @40°C	cSt	ASTM D7042	184
Kin. Viscosity @100°C	cSt	ASTM D7042	23.4
Viscosity Index		ASTM D2270	172
Viscosity CCS @-15°C	cP	ASTM D5293	7700
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	10.3
Sulphated Ash	%Wt	ASTM D874	1.5

